


Part Number : 19TR0A24  
 Serial Number : 19TRxA  
 LEDs Indicators



Mounting hole (inch)	0.3150"
Mounting hole (metric)	8mm
Indicator type	tri-color
Mounting type	with bezel
Bezel type	prominent
Bezel material	metal
Bezel color	satın chrome
Bezel size	M8
Protection	IP40
Lens type	round
Lens color	white diffused
Lens size	5mm
Connector Tpe	tab terminals 2.0x0.5mm
Connector number	3
Connector for lamp test	no
Number LED chip	2
Indicator color	red/green/yellow

Drawn : ROJ	Ch'd : ROJ	Datasheet : 19TRxA	Print date : 11/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :

**ELECTROSÓN**

Part Number : 19TR0A24  
Serial Number : 19TRxA  
LEDs Indicators

Dom wave length	625nm/568nm
Peak Wave Lenght (mA)	
Op. voltage (V)	24V DC
Forward volt max.	
Rectifier	
AC current	
DC current	20/20/40mA
Lum in min (mcd)	
Lum in type (DC)	10/20/30mcd
Voltage tolerance (%)	10%
Op. temperature (°C)	-25°C...+60°C
Storage temperature (°C)	-25°C...+60°C
Narrative	
Viewing angle (°)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 19TRxA	Print date : 11/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :

**ELECTROSÓN**