



PF1500



PTF1500



PTF1500

# FILTER FANS 100 m<sup>3</sup>/h

MODELS	UNIT	PF1500	PTF1500
AIR FLOW RATE	m <sup>3</sup> /h	-	100 (140)
POWER SUPPLY	V/Hz	-	230V 50-60Hz
DIMENSIONS	mm	160x160x31	160x160x69
POWER CONSUMPTION	W	-	26 (23)
CURRENT CONSUMPTION	A	-	0.14/0.13
OVERCURRENT PROTECTION	-	-	IMPEDANCE
ELECTRICAL CONNECTION	-	-	LEAD WIRE
OPERATING TEMPERATURE	°C	-10/+70	
PROTECTION DEGREE	-	IP54	IP54 / CLASS I
NOISE LEVEL	dB(A)	-	42 (46)
FLOW DIRECTION	-	-	OUTSIDE-IN
BEARING	-	-	BALL
PLASTIC MATERIAL	-	UL94 V0 ABS FLAME RETARDANT	
GASKET	-	POLYURETHANE SEALING	
COLOUR	-	RAL7035 (RAL7032 ON REQUEST)	
WEIGHT	kg	0.18	0.68
MOUNTING	-	FAST CLIP-ON	
CONFORMITY	-	CE	

