



PF12500



PTF2500



PTF2500

# FILTER FANS

115m<sup>3</sup>/h

MODELS	UNIT	PF12500	PTF2500
AIR FLOW RATE	m <sup>3</sup> /h	-	115 (130)
POWER SUPPLY	V/Hz	-	230V 50-60Hz
DIMENSIONS	mm	260x260x31	260x260x103
POWER CONSUMPTION	W	-	26 (23)
CURRENT CONSUMPTION	A	-	0.14/0.13
OVERCURRENT PROTECTION	-	-	IMPEDANCE
ELECTRICAL CONNECTION	-	-	3-POLE TERMINAL
OPERATING TEMPERATURE	°C	-10/+70	
PROTECTION DEGREE	-	IP54	IP54 / CLASS I
NOISE LEVEL	dB(A)	-	42 (46)
FLOW DIRECTION	-	-	OUTSIDE-IN
BEARING	-	-	BALL
PLASTIC MATERIAL	-	UL94 V0 ABS FLAME RETARDANT	
GASKET	-	POLYURETHANE SEALING	
COLOUR	-	RAL7035 (RAL7032 ON REQUEST)	
WEIGHT	kg	0.48	1.18
MOUNTING	-	FAST CLIP-ON	
CONFORMITY	-	CE	

